

Spiral Recoil Hose



Strong-Plus™ Spiral

Strong-Plus™ Spirals are manufactured with a proprietary process that allows reduced spiral diameter and increased retraction strength. Strong-Plus™ Spirals feature a soft, **5ft long polyurethane tail**, the Strong-Plus™ Spiral is ideal for fixed workspaces. The increased comfort and convenience offered by the tail combines the best traits of a straight hose and a spiral.

- Ideal for Painting and Finishing Applications
- Ultra-Flexible Tail
- Excellent Coil Memory and Retraction Strength
- Virtually Kink-Proof
- Reusable Nickel-Plated Fittings with Bend-Restrictors
- Thread Sealant Supplied on All Fittings

Specifications	
Material	Polyurethane (Ether-Based)
Hardness	Shore 98A / 60A
Temperature Range	-68°F to 140°F (-55°C to 60°C)
Working Pressure at 68°F	120 psi (8.2 Bar)
Vacuum Rating	28" HG
Safety Factor	3:1
Tariff Code	3917.33.0000

Fitting Compatibility
H & SH-Style Compression Replacement Fitting (Page 203, 204)

Note: Not all sizes available in all colors.
Please check for availability.



SP - 14 - 10 - OR - RR

Model		ID x OD (Nominal)		Total Length		Color		Fittings	
SP	Strong-Plus™ Spiral	316	3/16" x 5/16"	10	10 ft	OR	Orange	RR	Rigid & Rigid
		14	1/4" x 3/8"	15	15 ft	Y	Yellow		
		2164	21/64" x 1/2"	20	20 ft	LG	Light Green		
		1332	13/32" x 5/8"	25	25 ft	NB	Navy Blue		
		8	5mm x 8mm	2	2m				
		10	6.5mm x 10mm	4	4m				
		12	8mm x 12mm	6	6m				
		16	11mm x 16mm	8	8m				



Spiral Recoil Hose



Strong-Plus™ Spiral Fractional & Metric Sizes

Model (select color & fitting style)	ID	OD	Working Length	Thread	Compressed Length	Tool Tail Length	Port Tail Length	Total Turns	Spiral OD	Available Colors	Package Weight
SP-14-10-_-RR	0.250" (1/4")	0.375" (3/8")	8'	1/4" Male NPT	74.0"	64"	4"	15	1.62"	OR, LG,	0.69 lb
SP-14-15-_-RR			12'		83.5"			41			0.90 lb
SP-14-20-_-RR			16'		93.0"			66			1.13 lb
SP-14-25-_-RR			20'		103.0"			92			1.32 lb
SP-2164-10-_-RR	0.328" (21/64")	0.500" (1/2")	8'	3/8" Male NPT	74.0"	64"	4"	11	2.13"	OR, LG, NB	1.11 lb
SP-2164-15-_-RR			12'		83.0"			30			1.27 lb
SP-2164-20-_-RR			16'		93.0"			50			1.71 lb
SP-2164-25-_-RR			20'		102.5"			69			2.14 lb
SP-1332-10-_-RR	0.406" (13/32")	0.625" (5/8")	8'	1/2" Male NPT	74.0"	64"	4"	9	3.25"	LG, NB	1.75 lb
SP-1332-15-_-RR			12'		83.0"			24			1.99 lb
SP-1332-20-_-RR			16'		93.0"			40			2.23 lb
SP-1332-25-_-RR			20'		102.5"			55			2.46 lb
SP-10-2-_-RR	6.5mm	10mm	2.2m	1/4" Male BSPT (R)	140cm	160cm	10cm	20	40mm	OR, LG	0.75 lb
SP-10-4-_-RR			3.2m		160cm			40			0.90 lb
SP-10-6-_-RR			4.2m		180cm			60			1.00 lb
SP-10-8-_-RR			5.2m		200cm			80			1.19 lb
SP-12-2-_-RR	8mm	12mm	2.4m	3/8" Male BSPT (R)	144cm	160cm	10cm	20	50mm	OR, LG	2.00 lb
SP-12-4-_-RR			3.6m		168cm			40			3.00 lb
SP-12-6-_-RR			4.8m		192cm			60			3.38 lb
SP-12-8-_-RR			6.0m		216cm			80			4.50 lb

