

# POLYURETHANE TUBING

## Working Pressures

Size OD	75°F	150°F
<b>.125 (1/8")</b>	<b>240</b>	<b>100</b>
<b>.156 (5/32")</b>	<b>200</b>	<b>85</b>
<b>.187 (3/16")</b>	<b>150</b>	<b>90</b>
<b>.250 x 1/8" (1/4")</b>	<b>265</b>	<b>105</b>
<b>.250 x .160 (1/4")</b>	<b>180</b>	<b>70</b>
<b>.3125 (5/16")</b>	<b>175</b>	<b>75</b>
<b>.375 (3/8")</b>	<b>150</b>	<b>70</b>
<b>.500 (1/2")</b>	<b>150</b>	<b>70</b>
<b>.5625 (9/16")</b>	<b>140</b>	<b>60</b>
<b>.625 (5/8")</b>	<b>150</b>	<b>70</b>
<b>.750 (3/4")</b>	<b>140</b>	<b>70</b>
<hr/>		
<b>4mm</b>	<b>200</b>	<b>85</b>
<b>6mm</b>	<b>180</b>	<b>65</b>
<b>8mm</b>	<b>175</b>	<b>75</b>
<b>10mm</b>	<b>150</b>	<b>70</b>
<b>12mm</b>	<b>150</b>	<b>60</b>
<b>16mm</b>	<b>150</b>	<b>70</b>

WARNING: Improper selection or improper use of these products and/or systems described herein or related items can cause death, personal injury and property damage. This document and other information from ATP and our authorized distributors provide products and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the products and/or systems in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through their own analysis and testing, is solely responsible for making the final selection of the products and or/systems and assuring that all performance, safety and warning requirements of the application are met. The products are described herein, including and without limitation, product features, specifications, designs, availability and pricing, are subject to change by ATP and their authorized distributors without notice.