

The New Generation


FREE ANGLE®


The Improved, Ergonomic, Patented Swivel Fitting From ATP

FEATURES:

- Improved durability! A new steel cover protects rotating joint better than the original polyurethane cover.
- Two independent-rotation points allow a full 360° circular rotation and 45° angled rotation allows for better swivel action vs.
 Traditional swivel fittings.
- Prevents kinking of and strain on the supply line.
- Helps alleviate carpal tunnel syndrome and Back stress resulting in fewer lost-time injuries.
- Lightweight, streamlined design.
- Chrome-plated steel construction for long service life.
- Thread sealant is supplied on all male fittings.
- Many styles and sizes available for any application. Custom styles available with minimum quantity order.











USES:

- Automotive Assembly Operations
- Electronics Assembly Operations
 - Workstations
- Commercial & Residential Construction
 - Robotic Joints
 - Automotive Repair Facilities
 - Paint & Body Shops

SPECIFICATIONS:

| Media | Air Only |
|---------------------------|-----------|
| Working Temperature Range | 20°-140°F |
| Maximum Working Pressure | 145 PSI |
| Inner Diameter | 7.0mm |

MANUFACTURERS OF PRECISION-MADE POLYURETHANE SPIRAL HOSE & TUBING

The New Generation





Click on the part number to add the item to the shopping cart.

Male & Female

NFA N2M-N2M

| $\overline{}$ | | |
|---------------|----------------------|--|
| N | New Generation Model | |
| FA | Free Angle | |
| | | |

| F | |
|------|-----------------------|
| N | NPT Thread |
| | BSPT Thread (No Mark) |
| G | BSPP Thread (Special) |
| 1 | 1/8" Thread |
| 2 | 1/4" Thread |
| 3 | 3/8" Thread |
| M | Male Thread |
| F | Female Thread |
| or t | o add tha itam to the |

| \ | |
|----------|-----------------------|
| N | NPT Thread |
| | BSPT Thread (No Mark) |
| G | BSPP Thread (Special) |
| 1 | 1/8" Thread |
| 2 | 1/4" Thread |
| 3 | 3/8" Thread |
| M | Male Thread |

List Price

Click on the part number to add the item to the shopping cart.

Description

| M | W | | 10 |
|---|---|--|----|
| | | | |

| NFAN2M-N2M | 1/4" NPT Male x 1/4" NPT Male | \$ 21.26 |
|------------|---------------------------------|----------|
| NFAN3M-N3M | 3/8" NPT Male x 3/8" NPT Male | \$ 22.40 |
| NFA2M-2M | 1/4" BSPT Male x 1/4" BSPT Male | \$ 23.76 |
| NFA3M-3M | 3/8" BSPT Male x 3/8" BSPT Male | \$ 28.00 |



| NFAN2F-N1M | 1/4" NPT Female x 1/8" NPT Male | \$ 23.76 |
|------------|-----------------------------------|----------|
| NFAN2F-N2M | 1/4" NPT Female x 1/4" NPT Male | \$ 20.00 |
| NFAN2F-N3M | 1/4" NPT Female x 3/8" NPT Male | \$ 28.64 |
| NFAN3F-N3M | 3/8" NPT Female x 3/8" NPT Male | \$ 26.40 |
| NFA2F-2M | 1/4" BSPT Female x 1/4" BSPT Male | \$ 23.76 |
| NFA3F-3M | 3/8" BSPT Female x 3/8" BSPT Male | \$ 25.20 |

Click on the part number to add the item to the shopping cart.

Hose Barb

Part Number

| N | New Generation Model |
|----|----------------------|
| FA | Free Angle |
| В | Hose Barb |
| | |

| F | |
|----------|-----------------------|
| N | NPT Thread |
| | BSPT Thread (No Mark) |
| G | BSPP Thread (Special) |
| 1 | 1/8" Thread |
| 2 | 1/4" Thread |
| 3 | 3/8" Thread |

NFAB-N1M-2

| 2 | 1/4" I.D. Hose Barb |
|---|---------------------|
| 3 | 3/8" LD. Hose Barb |

Part Number


Description

Male Thread

List Price



| NFAB-N1M-2 | 1/4" Hose Barb x 1/8" NPT Male | \$ 23.40 |
|------------|--------------------------------|----------|
| NFAB-N2M-2 | 1/4" Hose Barb x 1/4" NPT Male | \$ 25.68 |
| NFAB-N2M-3 | 3/8" Hose Barb x 1/4" NPT Male | \$ 25.96 |
| NFAB-N3M-3 | 3/8" Hose Barb x 3/8" NPT Male | \$ 26.18 |



MANUFACTURERS OF PRECISION-MADE POLYURETHANE SPIRAL HOSE & TUBING

The New Generation

ADVANCED

Plug

NFAP-N2M-A210

| ▼ | |
|----|----------------------|
| N | New Generation Model |
| FA | Free Angle |
| Р | Plug |

| | * | |
|---|----------|-----------------------|
| | N | NPT Thread |
| | | BSPT Thread (No Mark) |
| | G | BSPP Thread (Special) |
| _ | 1 | 1/8" Thread |
| | 2 | 1/4" Thread |
| | 3 | 3/8" Thread |
| | М | Male Thread |

| A210 | ARO 210 Interchange |
|------|--------------------------------|
| C320 | European High Flow Interchange |
| C84 | ISO 6140C Interchange |
| JIS | Japanese Interchange |
| LN | Lincoln Interchange |
| UA | 1/4" US Industrial Interchange |
| UB | 3/8" US Industrial Interchange |

UA & UB

Click on the part number to add the item to the shopping cart.

| AF. | | | |
|-----|--------|--|------|
| I | | | |
| | Ci) Li | The state of the s | A210 |









| 1 | 1 | | |
|----|-------|---|----------|
| 11 | MEN 1 | 6 | |
| | | | TRUFLATE |

| Part Number | Description |
|-------------|-------------|
| | |

| NFAP-N1M-UA | 1/4" US Industrial Int. Plug x 1/8" NPT Male |
|----------------|--|
| NFAP-N2M-UA | 1/4" US Industrial Int. Plug x 1/4" NPT Male |
| NFAP-N3M-UA | 1/4" US Industrial Int. Plug x 3/8" NPT Male |
| NFAP-N2M-UB | 3/8" US Industrial Int. Plug x 1/4" NPT Male |
| NFAP-N3M-UB | 3/8" US Industrial Int. Plug x 3/8" NPT Male |
| NFAP-N2M-A210 | ARO 210 Interchange Plug x 1/4" NPT Male |
| NFAP-N2M-C320 | European High Flow Int. Plug x 1/4" NPT Male |
| NFAP-N2M-C84 | ISO 6150C Interchange Plug x 1/4" NPT Male |
| NFAP-2M-C84 | ISO 6150C Interchange Plug x 1/4" BSPT Male |
| NFAP-N2M-JIS | Japanese Interchange Plug x 1/4" NPT Male |
| NFAP-2M-JIS | Japanese Interchange Plug x 1/4" BSPT Male |
| NFAP-N2M-LN | Lincoln Interchange Plug x 1/4" NPT Male |
| NFAP-N2M-TRUFL | 1/4" Truflate Interchange Plug x 1/4" NPT Male |








Other Products From ATP


We at ATP believe we have developed the latest technology in tubing, hoses and pneumatic accessories. In keeping with current market demands, our products offer ergonomics and safety to help support assembly and automation applications.



Oetiker Swing Couplings ATP proudly carries and recommends Oetiker Swing **Couplings for use with our Free Angle Swivel Fittings. The ultimate** pairing where safety and ergonomics are concerned.



Polyurethane Spiral Hoses Standard, stock and our industry exclusive-the "Strong" and "Strong-Plus." Custom models are our specialty.



Tubing

- Polyurethane
- Polyethylene
- Nylon 12
- PTFE FEP
- PVC



Polyurethane Braided Hose Lightweight and flexible. Available in several durometers. Reinforced with nylon for greater working pressures.



Weld Tubing Metric, polyurethane tubing covered with a flame-resistant layer. Designed for robotic welding and other severe-service applications.



Hose & Tool Balancers Durable cases and high-quality internals make up our balancers. Ideal for workstation ergonomics.



Technibond® Thermally-bonded, polyurethane tube groupings available in straight and spiral configurations. A 5-conductor wire can be added to carry electric.



Blow Guns Lightweight, ergonomic designs available in die-cast and resin body styles.



Technifit™ Fittings Fractional & Metric push-toconnect fittings and speed controllers in both brass and resin materials, NPT & BSPT.



ARMOR-AIR™ Contractors Air Hose

Lightweight, flexible and much more abrasion-resistant than traditional rubber air hoses. A must-have for contractors, and anyone who owns an air compressor.



Hose Fittings Two-piece, reusable, compressionstyle brass fittings in fractional and metric, male and female, rigid and swivel.



Phone: 937.349.4055

Fax: 937.349.4155

TechniGrripp® The world's first hydraulic push-toconnect fitting. Does not require use of a crimper. Allows on-site fabrication of hoses to eliminate costly down time.

© Effective 06-2010 All Rights Reserved