

# Pneumatic Quick Disconnects



## Chrome-Plated Universal Couplings

ATP's Premium Series Quick Disconnects are precision machined, chrome-plated steel. These Automatic Universal couplers connect with the plug by simply pushing both units together. All 5SOC series couplers will connect to Industrial, TruFlate, ARO, European, and Lincoln Interchanges.

- Automatically Connects to Popular Interchanges
- Chrome-Plating Resists Corrosion, Easily Cleaned of Paint or Grease
- Steel Construction Maintains Integrity, not Easily Damaged like Brass
- Precision Machining Ensures Long Lasting, Leak-Free Connection.
- 6 Retaining Balls Prolong Seal life

Chrome-Plated Universal Couplings

Model	Thread	Interchange	Body Size	Hex	Length	OD
5SOC-N2F	1/4" Female NPT	Universal	1/4"	19mm	2.25"	0.94"
5SOC-N2M	1/4" Male NPT				2.36"	
5SOC-2B	1/4" Hose Barb				2.79"	
5SOC-H14	1/4" x 3/8" Compression				2.57"	
5SOC-N3F	3/8" Female NPT	Universal	1/4"	21mm	2.36"	0.94"
5SOC-N3M	3/8" Male NPT			19mm	2.87"	
5SOC-3B	3/8" Hose Barb				2.69"	
5SOC-H38	3/8" X 9/16" Compression					
5SOC-4B	1/2" Hose Barb	Universal	1/4"	19mm	2.99"	0.94"