

Free Fittings

Free-Elbow

Free Elbow™

The innovative design of the Free Elbow provides increased airflow compared to competing units. Two swivels along with a rotating joint provide an unrestricted range of motion for the user, reducing fatigue.



FEN2F - N2M

FE	Free-Elbow	N	NPT	N	NPT
		(Blank)	BSPT	(Blank)	BSPT
		2	1/4"	2	1/4"
		3	3/8"	3	3/8"
		4	1/2"	4	1/2"
		F	Female Thread	F	Female Thread
		M	Male Thread	M	Male Thread

Specifications	
Material	Chrome-Plated Steel
Maximum Working Pressure	145 psi
Temperature Range	23°F - 140°F
Media	Compressed Air
Seal Material	NBR- Rubber

Model	Thread 1	Hex 1	Thread 2	Hex 2	Length	O.D.
FEN2F-N2M	1/4" Female NPT	19mm	1/4" Male NPT	19mm	2.40" (60.9mm)	0.80" (20.3mm)
FEN3F-N3M	3/8" Female NPT	19mm	3/8" Male NPT	19mm	2.44" (61.9mm)	0.80" (20.3mm)
FEN4F-N4M	1/2" Female NPT	24mm	1/2" Male NPT	24mm	2.85" (72.3mm)	1.02" (25.9mm)
FE2F-2M	1/4" Female BSPT	19mm	1/4" Male BSPT	19mm	2.40" (60.9mm)	0.80" (20.3mm)
FE3F-3M	3/8" Female BSPT	19mm	3/8" Male BSPT	19mm	2.44" (61.9mm)	0.80" (20.3mm)
FE4F-4M	1/2" Female BSPT	24mm	1/2" Male BSPT	24mm	2.85" (72.3mm)	1.02" (25.9mm)